

Model: ZDADI3500-15-30

VPol 3400~3600MHz 30° 15dBi Wall Mount Antenna

Frequency Range-MHz3400~3600

Gain-dBi15

PolarizationVertical

Half-power Beam widthHor:30;Ver:32

VSWR≤1.5

Input impedance• 50

Maximum Input power-W100

Lightning ProtectionDC Ground

ConnectorN-F

Size-mm210*180*35


Weight-kg0.9

Radiating Element MaterialCu Ag


Reflector MaterialAluminum Alloy

Radome MaterialABS

Operating temperature;-40~60



水平面方向图
Horizontal pattern



垂直面方向图
Vertical pattern

Model: ZDAQI3500-03

VPol 3400~3500MHz 360° 3dBi Ceiling Mount Antenna

Frequency Range-MHz3400~3600

Gain-dBi3

PolarizationVertical

Half-power Beam widthHor:360;Ver:55

VSWR≤1.5

Input impedance• 50

Maximum Input power-W50

Lightning ProtectionDC Ground

ConnectorN-F

Size-mm58* ϕ 132


Weight-kg0.25

Radiating Element MaterialCn


Reflector MaterialElectrolysis Board

Radome MaterialABS

Operating temperature- $\text{j}\text{æ}$ -40~60



水平面方向图
Horizontal pattern



垂直面方向图
Vertical pattern